

# NATURALT TOUCH COLLECTION

**Pergo Naturaltouch** is a laminate floor intended for residential use.



The floor has a glue-free click system and built-in underlay.

## Product description

| Type               | Value  |
|--------------------|--|
| Dimension          | 1198 x 198 mm  |
| Thickness          | 9 mm   |
| Package            | Pack; 8 planks, 1,897 m <sup>2</sup> , Pallet; 40 packs, 75.88m <sup>2</sup> |
| Weight             | 8,0 kg/m <sup>2</sup> , 15,2 kg/pack, 623 kg/pallet                          |
| Surface            | SRS:G2, Wear protect AC5   |
| Surface texture    | Matt oiled texture   |
| Core material      | HDF Regular  |
| Backing            | SoundBloc CS (Compact SoundBloc)   |
| Joint              | Click system (Smartlock)   |
| Joint sealing      | Yes, Oil   |
| Built in SoundBloc | Yes (No extra underlay needed)   |

## Other information

- The normal way to install Pergo is in a random installation pattern.
- Pergo Installation instructions are to be followed as well as valid building standards.
- The temperature in the room shall at the time of installation be at least 15° C and RH 30-80%.
- Store the Pergo floor flat in unopened packages at normal room temperature, (>15°C) at least 0,5 m from the walls, for at least 48 h prior to installation.
- Check that the boards are undamaged and free from faults before installing.
- Pergo is suitable for use with hot water radiant floor heating. Electric radiant floor heating must be of self regulating type.
- Use felt pads and castor cups under furniture legs etc. A doormat should be used inside all external doorways to protect the floor.
- A separate maintenance guide exists.

# NATURALTOUCH COLLECTION


## Performance


| Type                             | Value                        | Testmethod |
|----------------------------------|------------------------------|------------|
| Class of use                     | 23 / 33                      | EN 13329   |
| Fire classification              | Not available                |            |
| Wear resistance                  | AC 5; $\geq 6500$ rev        | EN 13329   |
| Impact resistance                | IC 3                         | EN 13329   |
| Indentation resistance           | 0,0 mm                       | EN 13329   |
| Resistance to Rolling castor     | No damage                    | EN 13329   |
| Resistance to Furniture leg      | No damage                    | EN 13329   |
| Stain resistance                 | Group 1&2: 5, Group 3: 4     | EN 13329   |
| Resistance to burning cigarettes | Class 5                      | EN 13329   |
| Colour fastness/Fading           | Class 7                      | EN 13329   |
| Dimensional stability            | < 0,9 mm                     | EN 13329   |
| Surface soundness                | $\geq 1,0$ N/mm <sup>2</sup> | EN 13329   |
| Formaldehyde emission            | E 1                          | EN 717     |
| VOC emission                     | <0,05 mg/h m <sup>2</sup>    | FLEC       |
| Impact sound reduction           | 17-19 dB                     | ISO 717-2  |
| Slip resistance                  | R9                           | DIN 51139  |
| Thermal insulation               | 0,07 m <sup>2</sup> K/W      | DIN 52612  |
| Electro static resistance        | $3 \cdot 10^{12} \Omega$     | EN 1081    |
| Electrostatic charge             | 4 kV                         | EN 1815    |
| Density core material            | 870 kg/m <sup>3</sup>        |            |
| Thickness swelling               | < 12%                        | EN 13329   |





# NATURALT TOUCH COLLECTION


## Technical Features


- 


**The laminate floor with a matt oiled wood finish**  
Smooth/soft natural feeling  
A wooden floor feeling without the worries (easier to clean ,no need for re-oiling or sanding)
- 

**Best guarantee on the market**  
Full value, non declining, lifetime triple guarantee against wear, stain and fade
- 

**Superior durability for tough residential environments**  
Highest wear resistance AC5  
Best Scratch resistance “SRS G2”  
High impact resistance (HPL-multilayer laminate)
- 

**High moisture protection (Triple moisture protection system)**  
Tight joint construction  
Moisture resistant core  
Impregnated joints
- 

**Built in soundreduction**  
CS (Compact Soundbloc)  
50% reduction of the drumsound  
Improved sound caractersistics  
Impact sound reduction 17-19 dB
- 

**Easy and flexible installation (All in one)**  
Possible to either tap or fold  
No extra underlay needed (Built-in)
- 

**Matching accessories with highest durability**  
Perfect décor match  
Matching texture (moldings)  
Highest wear resistance, AC5 (moldings)  
Best scratch resistance ”SRS G2” (moldings)