

VINTAGE COLLECTION

Pergo Vintage is a laminate floor intended for residential use.



The floor has a glue-free click system and built-in underlay.

Product description

Type	Value
Dimension	1198 x 198 mm
Thickness	9 mm
Package	Pack; 8 planks, 1,90 m ² , Pallet; 40 pcs, 75,90 m ²
Weight	8,2 kg/m ² , 15,6 kg/pack, 639 kg/pallet
Surface	SRS:G2, Wear protect AC5
Surface texture	Structured texture
Core material	HDF Regular
Backing	SoundBloc CS (Compact SoundBloc)
Joint	Click system (Smartlock)
Joint sealing	Yes, Oil
Built in SoundBloc	Yes (No extra underlay needed)

Other information

- The normal way to install Pergo is in a random installation pattern. Under certain circumstances, preference should be given to a different type of installation pattern for aesthetic or technical reasons
- Pergo Installation instructions are to be followed as well as valid building standards.
- The temperature in the room shall at the time of installation be at least 18° C and RH 30-80%.
- Store the Pergo floor flat in unopened packages at normal room temperature, (>18°C) at least 0,5 m from the walls, for at least 48 h prior to installation.
- Check that the boards are undamaged and free from faults before installing.
- Pergo is suitable for use with radiant floorheating. Electrical floorheating must be of self regulating type. Check the fabricate and contact us for further information.
- Use felt pads and castor cups on furniture legs etc. A doormat should be used inside all external doorways to protect the floor.
- A separate maintenance guide exists.

VINTAGE COLLECTION


Performance


Type	Value	Testmethod
Class of use	23 / 33	EN 13329
Fire classification	Not available	
Wear resistance	AC 5; ≥ 6500 rev	EN 13329
Impact resistance	IC 3	EN 13329
Indentation resistance	0,0 mm	EN 13329
Resistance to Rolling castor	No damage	EN 13329
Resistance to Furniture leg	No damage	EN 13329
Stain resistance	Group 1&2: 5, Group 3: 4	EN 13329
Resistance to burning cigarettes	Class 5	EN 13329
Slip resistance	R9	DIN 51130
Colour fastness/Fading	Class 7	EN 13329
Dimensional stability	< 0,9 mm	EN 13329
Surface soundness	$\geq 1,0$ N/mm ²	EN 13329
Formaldehyde emission	E 1	EN 717
Impact sound reduction	17-19 dB	ISO 717-2
Thermal insulation	0,07 m ² K/W	DIN 52612
Electro static resistance	$3 \cdot 10^{12} \Omega$	EN 1081
Electrostatic charge	4 kV	EN 1815
Thickness swelling	< 12%	EN 13329





VINTAGE COLLECTION


Technical Feature


- 


A collection of planked rustic wood designs
 Décor and texture carefully selected to give a vintage atmosphere
 New modern floor that gives an antique feeling
- 

Best guarantee on the market
 Full value, non declining, lifetime triple guarantee against wear, stain and fade
- 

Superior durability for tough residential environments
 Highest wear resistance AC5
 Best Scratch resistance “SRS G2” (Patented)
 High impact resistance (HPL-multilayer laminate)
- 

High moisture protection (Triple moisture protection system)
 Tight joint construction (Patented)
 Moisture resistant core
 Impregnated joints
- 

Built in soundreduction
 CS (Compact Soundbloc)
 50% reduction of the drumsound
 Improved sound caractersistics
 Impact sound reduction 17-19 dB
- 

Easy and flexible installation (All in one)
 Possible to either tap or fold
 No extra underlay needed (Built-in)
- 

Matching accessories with highest durability
 Perfect décor match
 Matching texture (moldings)
 Highest wear resistance, AC5 (moldings)
 Best scratch resistance ”SRS G2” (moldings)