

COUNTRY COLLECTION

Pergo Country is a laminate floor intended for residential use.



TitanX SURFACE™



Product description

Type	Value
Dimension	1198 x 198 mm
Thickness	9 mm
Package	Pack; 8 planks, 1,90 m ² , Pallet; 40 packs, 75,88 m ²
Weight	8,0 kg/m ² , 15,2 kg/pack, 623 kg/pallet
Surface	TitanX
Surface texture	Textured surface, one décor with standard surface
Core material	HDF Moisture resistance
Backing	Soundbloc CS (Compact Soundbloc white)
Joint	Glue free Click system
Joint sealing	Yes
Bevelled edge	Yes, longside
Built in SoundBloc	Yes

Before installation

- Store the Pergo floor flat in unopened packages at normal room temperature, (>15°C) at least 0,5 m from the walls, for at least 48 hrs prior to installation.
- Pergo Country is suitable for use with hot water radiant floor heating. Electric radiant floor heating must be of self-regulating type

Installation

- The Pergo Country installation and maintenance instructions are to be followed as well as valid building standards.
- The temperature in the room shall at the time of installation be at least 15° C and RH 30-75%.

Floor conditions

- Use felt pads and castor cups under furniture legs etc. A doormat should be used inside all external doorways to protect the floor.
- The installed floor is designed for an indoor condition of relative humidity between 30 and 75 %. Humidity exceeding this will influence the performance of the floor.

COUNTRY COLLECTION


Performance

Type	Value	Standard
Class of use	23 / 32	EN 13329
Wear resistance	AC 4 ; ≥ 4000 rev	EN 13329
Impact resistance	IC 2	EN 13329
Indentation resistance	0,0 mm	EN 13329
Resistance to Rolling castor	No damage	EN 13329
Resistance to Furniture leg	No damage	EN 13329
Stain resistance	Group 1&2: 5, Group 3: 4	EN 13329
Resistance to burning cigarettes	Class 4	EN 13329
Colour fastness/Fading	Class 7	EN 13329
Dimensional stability	< 0,9 mm	EN 13329
Surface soundness	$\geq 1,0$ N/mm ²	EN 13329
Formaldehyde emission	E 1	EN 717
VOC emission	<0,05mg/h m ²	FLEC
Drum sound reduction	S ₁₀	EPLF
Impact sound reduction	17 - 19 dB	ISO 717-2
Slip resistance	Class DS	EN 14041
Slip resistance	$\mu_{\text{dry}} > 0,65$ (Low risk of slipping) $\mu_{\text{wet}} > 0,35$ (Moderate risk of slipping)	SlipAlert
Thermal insulation	0,07 m ² K/W	DIN 52612
Electrostatic resistance	$3 \cdot 10^{12} \Omega$	EN 1081
Electrostatic charge	4 kV	EN 1815
Density core material	> 850 kg/m ³	
Thickness swelling	< 12%	EN 13329




COUNTRY COLLECTION

Technical feature




A warm and cosy looking floor with bevel edges for a distinct feeling of a rustic wooden plank floor

Bevel edges on the long side only to enhance the feeling of long wooden planks.
 Textured surface for a rustic feeling




15 years Triple guarantee

Full value, non declining, triple guarantee against wear, stain and fade



Great durability for residential areas with TitanX Surface

High wear resistance AC4
 High scratch resistance
 High impact resistance (HPL-multilayer laminate)




High moisture protection (Triple moisture protection system)

Tight joint construction (Patented)
 Moisture resistant core
 Impregnated joints



Built in sound reduction


CS (Compact Soundbloc)
 Reduction of the drumsound
 Improved sound characteristics
 Impact sound reduction 17-19 dB



Easy and flexible installation (All in one)

Possible to either tap or fold
 No extra underlay needed (Built-in)*

* A 0,2 mm PE-foil is needed as a moisture barrier when installing on concrete subfloor or with floor heating



Matching accessories with highest durability

Perfect décor match
 Highest wear resistance, AC5 (moldings)
 Best scratch resistance "SRS G2" (moldings)